

## EMNİYET VENTİLİ SAFETY VALVE

USD



Basınç Sınıfı	: PN 16
Tip	: Oransal Kalkışlı - Tam Kalkışlı
Bağlantı	: Flanşlı DIN 2533
Ölçü	: DN 25 - DN 100
Gövde Malzemesi	: GG 25 - GGG 40
Boyut	: DIN 3202 - F 32 TS EN 558 (Seri 8)
Testler	: TS EN 12266-1
İç Aksam	: Paslanmaz Çelik
Uygulamalar	: Doymuş buhar sistemleri, sıcak ve soğuk su sistemleri, asit ve alkali özelliği olmayan sıvı akışkanlar
Çalışma Sıcaklığı	: -10...+120 °C (16 bar) , 300°C (10 bar)
Nominal Pressure	: PN 16
Type	: Proportional Lift - Full Lift
End Type	: Flange DIN 2533
Size	: DN 25 - DN 100
Body	: Cast iron - Ductile iron (GG 25 - GGG 40)
Dimensions	: DIN 3202 - F 32 TS EN 558 (Series 8)
Tests	: TS EN 12266-1
Seats	: Stainless Steel
Applications	: Saturated steam applications, Hot and cold water systems, non-acidic and non-flammable liquid fluids.
Working Temperature	: -10...+120 °C (16 bar) , 300°C (10 bar)



ÖLÇÜ SIZE	ORANSAL KALKIŞLI PROPORTIONAL LIFT	
	Nes 2007 YAYLI SPRING	Nes1976 AĞIRLIKLI WEIGHTED
	FİYAT ( \$ ) PRICE	FİYAT ( \$ ) PRICE
25/25		
32/32	Please ask for prices	Please ask for prices
40/40		
50/50		
65/65		
80/80		
100/100		

ÖLÇÜ SIZE	TAM KALKIŞLI FULL LIFT	
	Nes 2013 YAYLI SPRING	Nes 2009 AĞIRLIKLI WEIGHTED
	FİYAT ( \$ ) PRICE	FİYAT ( \$ ) PRICE
25/40		
32/50	Please ask for prices	Please ask for prices
40/65		
50/80		
65/100		
80/125		
100/150		